

**GP360**<sup>D</sup>

Comfortable, compact and compliant, easily towed and secured in minutes saving time and money.

The single axle Groundhog Mobile Welfare Unit GP360D is a lightweight and compact towable unit that meets HSE & CDM requirements and provides all your on-site needs in one small package.

The units are suitable for accommodating six people, which provides pleasant and safe working environments, ideal for rental companies and contractors.

Easily towed, one man operation secured and manoeuvred on site, in less than 3 minutes. Its' many safety features make it a high secure and money saving choice of welfare unit.

- > Warm water supplied by an on-board heating system
- > Spacious, well equipped canteen / 6 person seating area
- > Secured in less than 3 minutes
- > High security doors and windows
- > Meets HSE & CDM requirements

# **Specifications**

- > Dimensions:
- 3655mm (L) x 2300mm (W)\*
- > Dimensions including drawbar: 4920mm (L) x 2300mm (W)\*
- > Net Weight: 1700kg\* > Gross Weight: 1800kg





The GP360<sup>D</sup> complies with Health & Safety regulations which guarantees certain facilities for contractors working on site.

**Regulation 20** Sanitary Conveniences **Regulation 21** Washing Facilities


Provision for Drinking Water **Regulation 22 Regulation 23** Provision for Drying Clothing

Facilities for Changing Clothing Regulation 24 **Regulation 25** Facilities for Rest & to Eat Meals

on all our ranges







# 1. Welfare Area

- Table and bench seating for up to 6 people
- Microwave and kettle both hard-wired
- Fresh and waste water containers (20L cap each)
- Warm water supplied by on-board heating system
- Large stainless steel sink c/w warm water tap
- 12V pump for water system
- 500W electric wall mounted heater
- 240V 600mm strip light
- Single 2Amp socket outlet
- Consumer board c/w RCD & MCB's
- Generator control panel with hour run meter
- Paper towels, liquid soap and cup dispenser
- Carbon monoxide monitor and smoke alarm
- Fresh drinking water container (20L)
- High level vent

### 2. Toilet Area

- Plastic recirculating toilet c/w ventilation pipe
- Forearm pedestal wash basin c/w warm water tap
- Toilet tank size: 280L
- Toilet roll holder
- 12V LED light with PIR
- Warm water tap supplied by on-board heating system
- Liquid soap & paper towel dispenser

### 3. Warm Room / Generator Area

- Bulkhead light 240V
- 240V tubular heater
- Coat hooks
- Ventilation panel
- 6kVA diesel generator with exhaust venting through roof area
- Access to fuel tank with separate fuel level gauge (fuel tank capacity = 58L)
- Fuel tank runtime = approx. 25 hours
- Fuel Active system



## Secured in less than 3 minutes

Easily towed, one man operation secured and manoeuvred on site. Its many safety features make it a high secure and money saving choice of welfare unit for rental companies and contractors.



Unhitch from towing vehicle and operate hydraulics using the push button controls

3 min