

GSO600 Luxury Solar Office

For full details on all our ranges please visit our website at www.groundhog.co.uk

The latest concept in solar technology, the unit has good economic use of space and delivers cost effective, environmentally efficient, robust luxury static office accommodation.

Groundhog GSO600 Luxury Solar Office

The units are powered by solar technology, with generator backup, and comes equipped with many space saving features including warm water supplied by on-board heating system, large stainless steel sink, storage under worktop, air blown heating system, cool box, lighting and double power sockets as standard, coat hooks and notice board – all these features provide a pleasant environment for office use.

- > Solar technology
- > Warm water supplied by an on-board heating system
- > Air blown heating system
- > Comfortably sits up to 4 people
- > Low level lifting
- > High security doors and windows
- > Meets HSE requirements













Specifications

Dimensions: 6100mm (L) x 2755mm (W)*

1. Welfare/ Office Area

- Pleasant and light office space
- Double glazed PVC windows
- Security roller shutters, which when closed are secured internally
- Air blown heating system
- Warm water supplied by on-board heating system
- Large stainless steel sink c/w hot water tap
- Kettle on fused spur switch
- 12 Volt L.E.D. lighting c/w PIR sensor
- Inverter powered double socket c/w USB connectors
- Generator control panel with hour run meter
- Felt notice board
- Cool box
- Carbon monoxide monitor and smoke alarm
- High/ low level vent
- Storage cupboard with shelving
- Voltmeter
- Insulated multi-point locking security door

2. Toilet Area

- Full flush toilet
- 180L waste tank below floor
- Ceramic basin with warm water tap
- Warm water supplied by on-board heating system
- Toilet roll holder
- 12 Volt L.E.D. lighting c/w PIR sensor
- Ventilation panel
- Paper towel & soap dispenser
- 12 Volt extractor fan
- Mirror

3. Generator Area

- 6kVA super silent diesel generator with aluminium exhaust box and ventilation
- 2 x 165Amp hour batteries
- 200 litre diesel tank and bund with filler neck and level gauge with Fuel Active system
- 12 Volt 30Amp battery charger
- Battery guard with fuse panel
- Fresh water tank
- Consumer Board c/w RCD & MCB's
- 1600W inverter and solar panel regulator







