

SW6100 Fusion Range

For full details on all our ranges please visit our website at www.groundhog.co.uk

The Groundhog

Static SW6100

Fusion range is incredibly efficient and incorporates all the latest environmental & safety technologies.

Groundhog SW6100 Fusion

The Fusion offers all the benefits of the standard SW6100 whilst offering a green environmental solution. This gives owners and end users savings by way of reduced fuel usage, reduced generator servicing, longer generator life, fewer breakdowns and massively reduced noise pollution.

- > Warm water supplied by an on-board heating system
- > Air blown heating system
- > Spacious, well equipped Canteen / Seating Area
- > Comfortably sits up to 8 people
- > High security doors and windows
- > Meets HSE & CDM requirements
- > Fixed low level lifting & fork pockets





Value Proposition





£1,750



breakdown costs saving of £1,200

Low noise pollution

Figures are for guidance only. For your own specific savings, contact Genquip for your bespoke value proposition.

Specifications

- Dimensions: 6100mm (L) x 2755mm (W)*
- > Net Weight: 4,200kg*

1. Welfare Area

- Pleasant and light rest area
- Table and bench seating for up to 8 people
- Air blown heating system
- Warm water supplied by on-board heating system
- Large stainless steel sink c/w warm water tap
- Microwave and kettle both hard-wired
- Fresh & waste water containers (20 Ltr cap each)
- 12V LED lighting with PIR
- 1 x single inverter powered socket
- 12V socket and USB connection (optional)
- Consumer board c/w RCD & MCB's
- Generator control panel with hour run meter
- Paper towel dispenser
- Liquid soap dispenser
- Disposable cup dispenser
- Carbon monoxide monitor and smoke alarm
- High level vent
- 1000mm base unit c/w 10L water heating system
- 12V control panel c/w heater control and battery volt meter
- 6 x 4 felt notice board

2. Drying Area

- 12V LED lighting with PIR
- Air blown heating system
- Coat hooks
- Bench seating
- High level window

3. Toilet Area

- Plastic recirculating toilet c/w ventilation pipe
- Forearm pedestal wash basin c/w warm water tap
- Toilet tank size: 280L
- Warm water supplied by on-board heating system
- Toilet roll holder
- 12V LED lighting with PIR
- Liquid soap & paper towel dispenser
- Mirror

4. Generator Area

- 6kVA super silent diesel generator with exhaust outlet and ventilation
- 9.8kVA super silent diesel generator with exhaust outlet and ventilation (optional)
- 12V generator start battery
- 200 litre diesel tank with filler neck and level gauge with Fuel Active system
- Fuel tank runtime = approx. 105 hours
- 12V LED lighting with PIR
- 130Amp hour battery
- 12V 30Amp battery charger
- Battery guard with fuse panel









20 21