



SW6100 Standard Range

For full details on all our ranges please visit our website at www.groundhog.co.uk

The Groundhog **Static SW6100** product range is incredibly robust and efficient incorporating all the latest standard features.



Groundhog Standard SW6100

The Standard SW6100 accommodates 8 people and provides a pleasant, spacious, restful environment, ideal for construction, rail and highways contractors.

Once lifted into position, the unit provides a vandal resistant accommodation and comes fitted with features such as a standard recirculating toilet, the latest warm water heating system, wall mounted heaters, microwave and kettle which are powered by an on-board 9.8kVA generator.

- > Warm water supplied by an on-board heating system
- > Spacious, well equipped Canteen / Seating Area
- > Comfortably sits up to 8 people
- > High security doors and windows
- > Meets HSE & CDM requirements

The SW6100 complies with Health & Safety regulations which guarantees certain facilities for contractors working on site.

Regulation 20	Sanitary Conveniences	✓
Regulation 21	Washing Facilities	✓
Regulation 22	Provision for Drinking Water	✓
Regulation 23	Provision for Drying Clothing	✓
Regulation 24	Facilities for Changing Clothing	✓
Regulation 25	Facilities for Rest & to Eat Meals	✓

Specifications

- > Dimensions: **6120mm (L) x 2755mm (W)***
- > Net Weight: **4,000kg***

1. Welfare Area

- Pleasant and light rest area
- Table and bench seating for up to 8 people
- Oil filled radiator
- Warm water supplied by on-board heating system
- Large stainless steel sink c/w warm water tap
- Microwave and kettle – both hard-wired
- Fresh & waste water containers (20 Ltr cap each)
- 1 x 230V double socket
- Consumer board c/w RCD & MCB's
- Hour run meter on generator
- Paper towel dispenser
- Liquid soap dispenser
- Disposable cup dispenser
- Carbon monoxide monitor and smoke alarm
- High level vents
- 1000mm base unit c/w 10L water heating system
- 230V strip lighting

2. Drying Area

- 230V tubular heater
- High level window
- Coat hooks
- 230V strip lighting
- Generator service hatch
- Bench seating

3. Toilet Area

- Plastic recirculating toilet c/w ventilation pipe
- Forearm pedestal wash basin c/w warm water tap
- Toilet tank size: 280L
- Warm water supplied by on-board heating system
- Toilet roll holder
- 230v bulkhead light
- Liquid soap & paper towel dispenser

4. Generator Area

- 9.8kVA super silent diesel generator with exhaust outlet and ventilation
- 230v bulkhead light
- 300 litre diesel tank with filler neck and level gauge
- 3mm thick O/P (over-plain) diamond durbar plate flooring
- Generator hour run meter
- Generator start battery
- Fuel tank runtime = approx. 120 hours

