









## Innovative, functional, environmentally efficient and cost effective.

The mobile **groundhog** anti-vandal twin toilet unit has an in-built effluent tank, so there is no need to hire separate effluent tanks saving you time and money.

Robust and incredibly efficient, this unit offers huge reductions in fuel usage, carbon emissions and service

Incorporating the latest environmental solar technology, the groundhog twin toilet unit is ideal for the ever increasing demands of the construction, rail, utility and hire industry.



Powered by two solar panels



12V LED lighting with PIR



Warm wash set over large stainless steel sink



windows c/w

security frame

x2 low flush

Fully hot-dipped

galvanised



appliance inlet in lockable box





Easy manoeuvrability

## KEY FEATURES at a glance

For full specification, please visit www.groundhog.co.uk



Length	<b>3000</b> mm
Length (including drawbar)	<b>4299</b> mm
Height (on wheels)	<b>2.9</b> m
Height (on ground)	<b>2.5</b> m

Unladen Weight	<b>1690</b> kg
Possible Gross Weight *Unit should be towed dry at all times	<b>2490</b> kg*
Solar Panel x2	x <b>2</b>

Inverter	<b>2</b> W
Fresh Water Container	<b>2</b> x <b>20</b> Litres
Fresh Water Tank	<b>2 x 200</b> Litres
Under Floor Waste Tank	<b>2 x 200</b> Litres

\* Fully laden gross weight exceeds maximum towing capacity, unit should be transported to site prior to making site ready



1	Toilet Area
Full Flush Toilet	
Large Stainless Steel Sink C/W Warm Water Tap	
Liquid soap dispenser	
200 Litre Fresh Water Tank	
200 Litre Under floor Waste Tank	
Was	te outlet
200 200	uid soap dispenser  Litre Fresh Water Tank  Litre Under floor Waste Tank

Waste outlet	
2 Toilet Area	
Full Flush Toilet	
Large Stainless Steel Sink C/W Warm Water Tap	
Liquid soap dispenser	
200 Litre Fresh Water Tank	
200 Litre Under floor Waste Tank	
Waste outlet	

3	Lockable access area under worktop
12V	Water Pump
240AH Battery	
Hydraulic Power Pack	
Solar Charge Regulator	
375W Inverter	
Battery Charger	

Flooring
Recycled Non-Slip Flooring
Internal construction

Lined and Insulated in GRP, panels with block

Road lighting

External construction

Single axle trailer

Low level lifting eyes

High level lifting eyes

Fork pockets

Steel profiled panels to side walls and roof
Steel personnel doors to two separate areas (Toilet

High level windows c/w security frame

2 x 425 Watt Solar panels fitted to roof

Easy access wheel removal

16 Amp appliance inlet c/w lockable steel box

12 Volt fixed lighting c/w number plate bracket















