

SW6100D

Anti-Vandal, Robust
and Easy-To-Use **Static**
Welfare Accommodation Unit.

HSE
& CDM
COMPLIANT



STANDARD

STATIC

SEATS UP TO
8 PEOPLE



INNOVATION THAT WORKS.



Seating area



Toilet wash area



Delivery of hot water



Well equipped canteen

**Incredibly robust and efficient
incorporating all the latest
standard features.**

The Standard SW6100 from **groundhog** accommodates 8 people and provides a pleasant, spacious, restful environment, *ideal for construction, rail and highways contractors.*

Once lifted into position, the unit provides a vandal resistant accommodation and comes fitted with features such as a standard recirculating toilet, the latest warm water heating system, wall mounted heaters, microwave and kettle which are powered by an on-board 9.8kVA generator.



Recycled
non-slip
flooring



Down flow
heaters



10L 230V water
heating system c/w
12V water pump



Separate
drying room



9.8kVA super silent
diesel generator



240V
strip lighting

KEY FEATURES at a glance

For full specification, please visit
www.groundhog.co.uk



Length	6100 mm
Width	2755 mm
Height	2.5 m

Generator	9.8 kVA
Unladen Weight	4000 kg
Possible Gross Weight	4300 kg
Solar Panel	N/A

Fresh Water	20 Litres
Waste Water	20 Litres
Toilet Tank Size	280 Litres
Fuel Tank Size	300 Litres



1 Canteen Area

Pleasant and light rest area
Table and bench seating for up to 8 people
Down flow heaters
Warm water supplied by on-board heating system
Large stainless steel sink c/w warm water tap
Microwave and kettle – both hard-wired
Fresh & waste water containers (20 Ltr cap each)
1 x 230V double socket
Consumer board c/w RCD & MCB's
Paper towels, liquid soap and cup dispenser
Carbon monoxide monitor and smoke alarm
High level vents
1000mm base unit c/w 10L water heating system
230V strip lighting
6x4 felt noticed board

2 Generator Area

9.8kVA super silent diesel generator with exhaust outlet and ventilation
230V bulkhead lighting
300 litre diesel tank with filler neck and level gauge
3mm thick O/P (over-plain) diamond durbar plate flooring
Generator hour run meter
Generator start battery
Fuel tank runtime = approx. 120 hours

3 Toilet Area

Plastic 280L recirculating toilet c/w ventilation pipe
Forearm wash basin c/w warm water tap
Warm water supplied by on-board heating system
230V bulkhead lighting
Liquid soap & paper towel dispenser

4 Drying Room

Down flow heaters
High level window
Coat hooks
230V strip lighting
Generator service hatch
Bench seating